

# TAKE A **10-MINUTE** TEST TO CHECK FOR **TOILET LEAKS**



1

Drop a dye tablet or add a few drops of food coloring into the tank at the back of your toilet and wait 10 minutes.

2

If the color shows up in the bowl, you have a leak that can probably be fixed by replacing a worn toilet flapper.

3

Don't forget to flush the toilet afterwards to remove any dye in the bowl.

# TAKE A **10-MINUTE** TEST TO CHECK FOR **TOILET LEAKS**



1

Drop a dye tablet or add a few drops of food coloring into the tank at the back of your toilet and wait 10 minutes.

2

If the color shows up in the bowl, you have a leak that can probably be fixed by replacing a worn toilet flapper.

3

Don't forget to flush the toilet afterwards to remove any dye in the bowl.



LEARN HOW TO GET A  
HANDLE ON LEAKS AT  
[www.epa.gov/watersense](http://www.epa.gov/watersense)



LEARN HOW TO GET A  
HANDLE ON LEAKS AT  
[www.epa.gov/watersense](http://www.epa.gov/watersense)

# MORE 10-MINUTE TASKS

**CHECK**



Check for leaks. Indoors, look for dripping faucets, showerheads, and listen for running toilets. Outdoors, check irrigation systems, sprinklers, and spigots or hose bibbs.

**TWIST**



Twist and tighten faucet, showerhead, hose, and pipe connections to stop drips. To save more water, twist a WaterSense labeled aerator on to your bathroom faucet.

**REPLACE**



If your toilet keeps running long after your flush, you may need to replace a worn toilet flapper, the rubber ball attached to a chain in your toilet tank.

FOR MORE TIPS ON FIXING LEAKS, VISIT <https://www.epa.gov/watersense/fix-leak-week>



# MORE 10-MINUTE TASKS

**CHECK**



Check for leaks. Indoors, look for dripping faucets, showerheads, and listen for running toilets. Outdoors, check irrigation systems, sprinklers, and spigots or hose bibbs.

**TWIST**



Twist and tighten faucet, showerhead, hose, and pipe connections to stop drips. To save more water, twist a WaterSense labeled aerator on to your bathroom faucet.

**REPLACE**



If your toilet keeps running long after your flush, you may need to replace a worn toilet flapper, the rubber ball attached to a chain in your toilet tank.

FOR MORE TIPS ON FIXING LEAKS, VISIT <https://www.epa.gov/watersense/fix-leak-week>

