



Single-Family Dwelling Erosion Control Affidavit



**Field
Operations**

Bryce A. Stuart Municipal Building
Suite 328
100 E. First Street
Winston-Salem, NC 27101

P.O. Box 2511
Winston-Salem, NC 27102-2511

This affidavit must be submitted at the time of the building permit application.

Phone: 311 or (336) 747-7453
Fax: (336) 727-2792

Date: _____ Permit #: _____

Job Site Address: _____

Subdivision Name: _____ Parcel Pin # _____

Land area to be disturbed during construction (sq. ft. or acres): _____

General Contractor: _____

Address: _____

City/State/Zip: _____ Office Phone: _____

Mobile Phone: _____ Fax Number: _____ Email: _____

My signature hereto signifies I am the owner/financially responsible party for job site compliance with the Erosion Control Ordinance as outlined in Chapter, Section 4 of the Unified Development Ordinances (UDO) of the City of Winston-Salem/Forsyth County or Article IV of the UDO of the Village of Clemmons, Town of Lewisville, or Town of Walkertown. I hereby acknowledge that Best Management Practices must be used to control soil erosion on my job site to include but not be limited to the following:

1. Installation and regular maintenance of silt fencing using the preferred method of trenching installation on all low/down slope sides of my job site. Silt fence is to have an upslope return at each end no less than 5 feet. Silt Fence must be installed to meet the minimum standards as specified in the North Carolina Erosion and Sediment Control Planning and Design Manual Section 6.62 (Link: <http://deq.nc.gov/about/divisions/energy-mineral-land-resources/energy-mineral-land-permit-guidance/erosion-sediment-control-planning-design-manual>); and
2. Installation and regular maintenance of a stone construction entrance. The stone construction entrance shall consist of a 2 inch to 3 inch coarse washed aggregate stone. Construction entrance shall be a minimum 6 inches in thickness, minimum of 12 foot wide extended to the structure or 50 feet in length if site conditions allow, and have geotextile fabric under liner; and
3. Removal of mud and sediment from the street or adjacent property(ies) immediately following such an occurrence; and
4. Conduct no land disturbing activity within 15 feet of the banks of streams, lakes, wetlands or other water courses or water bodies; and
5. Provide adequate vegetative cover on any unstabilized areas to provide an effective barrier from erosion; and
6. Install any other measures as deemed necessary by representatives of the Erosion Control Division.

I understand that if the total disturbed area for any reason becomes greater than 20,000 square feet, including other lots I have under construction within a common plan of development, a formal Erosion Control Plan will be required to be submitted and approved in order to obtain a Grading/Erosion Control Permit. I further acknowledge that City Inspection's staff may refuse to make building inspections and the Erosion Control Division may issue Notices of Violation, Stop Work Orders and/or Civil Penalty Assessments for failure to comply with Erosion Control requirements. I also acknowledge that Grading/Erosion Control Permit fees will be doubled if work starts before obtaining a permit where one is required.

Signature

Print Name

Title

Date Signed